

NH fuse enclosure

# GST 4325-250

## GST 4325-250

NH fuse enclosure

CUSTOMIZABLE

Productnumber: 04642501

Dimensions: 640 x 320 x 179 mm

busbar enclosure, equipped with 2 x NH 000 fuse switch disconnecter, Elevator clamp 1.5 - 50 mm<sup>2</sup>, bottom side output, 5-pole busbar, with 5 busbar terminals for direct connection of a cable to the busbar system, additional N and PE terminal for each switch, 4 x enclosure connectors (GGV)

busbar system 250 A, with transparent cover



## Technical Data

### electrical characteristics

Rated operating voltage AC:	690 V
Protection class:	II
Type of protection:	IP65
Rated current:	250 A
UL Type Rating:	3R

### Dimensions

Width:	640 mm
Length:	320 mm
Height:	179 mm
Weight:	9.7 kg

### Material characteristics

UV-resistant:	yes
Halogen free:	yes
Glow-wire flammability according to EN 60695-2-11:	960 °C

### mechanical properties

Impact strength:	IK08
Cover screw torque:	2.5 Nm

### Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C
Installation location:	protected outdoor areas

## Sales Information

EAN:	4013902689323
Packing Unit Code:	CT
ETIM Class:	EC000249
Custom tariff number:	85369095

## Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate, glass-fibre reinforced
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced

## Accessories

[07251401 - GFS 14-m - Flange set](#)

[07505601 - GSV 56 - Busbar connector](#)