

## PRODUCTINFORMATIEBLAD DALIECO BT CONTROL

DALIECO BT CONTROL | Besturingseenheden voor lichtmanagementsystemen



### Toepassingsgebieden

- Floor-standing luminaires
- Meeting rooms
- Conference rooms
- Training rooms
- Classrooms
- Corridors
- Shop lighting

### Productvoordelen

- Control the light via Smartphone
- Adjustment of all settings via smartphone
- Plug and Play: Basic features usable without App
- Simplified startup thanks to predefined operation modes
- Intuitive manual dimming, switching and changing of colour temperature
- Up to 4 groups separately controllable
- Adjustable Offset for different groups
- Easy Scene creation via App
- Scene-recall via OSRAM DALI PRO PB coupler possible
- Firmware update over-the-air via Bluetooth possible
- Integrated DALI supply
- Control of standard white or Tunable White light acc. DALI device type 8 (DT8)\*
- Selected DALI parameters changeable via APP

### Productkenmerken

- Compact light control with DALI interface
- Smart phone connection via Bluetooth to control and configure
- One DALI output channel (Broadcast or Groupcast)
- Up to 32 DALI luminaires connectable
- Supports up to 4 OSRAM DALI sensors and pushbutton couplers


- Daylight-dependent regulation and presence-dependent control of light
- Separate pushbutton input to operate via standard pushbutton
- Supports DALI DT8 Tunable White driver
- Outputs with electronical reversible overtemperature, short-circuit, overload protection
- Length of the DALI control cable: up to 300 m
- Length of the pushbutton cable: up to 50 m
- Suitable for luminaire integration

## TECHNISCHE GEGEVENS

## ELEKTRISCHE GEGEVENS

Nominale vermogen	3,00 W
Nominale spanning	230 V
Netfrequentie	50/60 Hz
Werk frequentie	50/60 Hz

## AFMETINGEN &amp; GEWICHT



Lengte	108,00 mm
Breedte	31,00 mm
Breedte (incl. ronde armaturen)	31.00 mm
Hoogte	21,00 mm
Hoogte (incl. cylin. armaturen)	21.00 mm
Product gewicht	45,00 g

## TEMPERATUREN &amp; BEDRIJFSOMSTANDIGHEDEN

Omgevingstemperatuur bereik	-20...+60 °C
-----------------------------	--------------

## AANVULLENDE PRODUCTGEGEVENS

Commissioning tool	App (Android/iOS)
Max. connectable push button couplers	4
Number of connectable sensors	4
Groups	4

## MOGELIJKHEDEN

Dimbaar	Nee
Dimmer interface	DALI
Aantal stuuruitgangen	1
Type montage	Inbouwarmatuur/Onafhankelijke montage
Zendbereik	15 m

## CERTIFICATEN &amp; NORMEN






Keurmerken	CE
------------	----

Veiligheidsklasse	II
Type bescherming	IP20

### Technische uitrusting

- Free App for iOS and Android available at the app store
- Ceiling or independent installation via ECO CI KIT possible

### DOWNLOADS

Documenten en certificaten	
	User instruction
	Declarations Of Conformity CE
	Declarations Of Conformity UKCA
	Certificates
CAD/BIM-bestanden	
	CAD_STEP_3D

### LOGISTIEKE GEGEVENS

Productcode	Verpakkingseenheid (stuks per verpakking)	Afmetingen (lengte x breedte x hoogte)	Brutogewicht	Volume
4052899988781	Vouwdoos 1	160 mm x 35 mm x 40 mm	75.00 g	0.22 dm <sup>3</sup>
4052899988798	Verzenddoos 25	223 mm x 197 mm x 179 mm	2006.00 g	7.86 dm <sup>3</sup>

De genoemde productcodes beschrijven de kleinste hoeveelheid die besteld kan worden. Eén verzendenheid kan bestaan uit één of meer afzonderlijke producten. Bij het plaatsen van een order enkele of veelvouden van de verpakkingseenheid invoeren.

### DISCLAIMER

Onder voorbehoud van verandering zonder kennisgeving. Fouten en drukfouten voorbehouden. Zorg ervoor dat u de meest recente versie gebruikt.