Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or trade mark: F | PHILIPS |
|----------------------------------|---------|
|----------------------------------|---------|

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

| _ | • | | | |
|------|----|-------|--------|-----|
| Tyna | Λt | lioht | source | ٠. |
| IVDE | vı | HEILL | JUUILE | - • |

| Lighting technology used: | LED | Non-directional or directional: | NDLS |
|-------------------------------|--------|---------------------------------|------|
| Light source cap-type | G24D-1 | | |
| (or other electric interface) | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | No |
| | | | |

Product parameters

| Parameter | | Value | Parameter | Value |
|-----------------------------------|--|-------------------------|--|-----------|
| General product parameters: | | | | |
| | mption in on- 100 h), rounded st integer | 5 | Energy efficiency class | F |
| indicating if it r in a sphere (3 | us flux (фuse), efers to the flux 60º), in a wide n a narrow cone | 500 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000 |
| On-mode pressed in W | oower (P _{on}), | 4,5 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 |
| for CLS, expres | dby power (P _{net}) ssed in W and second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 80 |
| Outer | Height | 138 | Spectral power | See image |
| dimensions | Width | distribution in the | in last page | |
| without | Depth | 34 | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | | range 250 nm to 800 nm, at full-load | |
|--|------|---|-------|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - |
| | | Chromaticity | 0,382 |
| | | coordinates (x and y) | 0,380 |
| Parameters for LED and OLED light sources: | | | |
| R9 colour rendering index value | 0 | Survival factor | 0,90 |
| the lumen maintenance factor | 0,96 | | |

(a)'-': not applicable; (b)'-': not applicable;

