

WLD+70024NW

WLD+70024NW



Power **7 W**

Colour temperature **4000 K**

Beam angle **80 °**

Voltage **48 V**

Colour of light **Neutral white**

Degree of protection (IP) **IP20**

Technical data


| | |
|------------------------------|------------------------|
| Code | WLD+70024NW |
| Power | 7 W |
| Nominal current | 120 mA |
| Voltage | 48 V |
| Energy consumption | 7 kWh/1000h |
| Frequency | DC Hz |
| Protection class | III |
| Power factor | 1 |
| Useful luminous flux* | 700 lm (360°) |
| Luminous flux** | 300 lm (360°) |
| Lamp efficacy | 100 lm/W |
| Luminous intensity | 150 cd |
| Colour temperature | 4000 K |
| Colour of light | Neutral white |
| Beam angle | 80 ° |
| RA | 80 |
| Light source included | Yes |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20 to +40 ° |
| Lifespan | 17000 h |
| Housing material | AL+PC |
| Degree of protection (IP) | IP20 |
| Colour | Czarny |
| Dimension (AxBxC) | 55x95 (1100mm wire) mm |
| For use | Inside |
| Assembly method | NA SZYBĘ |
| Application | Inside |
| Made in | PRC |

Related documents



 User manual



 Declaration of Conformity