

| | | |
|---------------------------|--------------------------------------|---|
| 11201000 | DATA SHEET |  |
| Valid from: 17.09.2018 | EPIC® MC 2.5 STAMPED CONTACTS | |

Description

- For inserts and modules of the EPIC® rectangular connectors



| Article-Number | Article | Version | Conductor cross-section(mm ²) | Surface | Stripping length (mm) |
|-----------------|----------------|---------|---|---------|-----------------------|
| Contacts | | | | | |
| 11201000 | MC 2,5 stamped | Male | 0,5-1,5 | Ag | 3,5+0,5 |
| 11205000 | MC 2,5 stamped | Female | 0,5-1,5 | Ag | 3,5+0,5 |
| 11202000 | MC 2,5 stamped | Male | 1,5-2,5 | Ag | 3,5+0,5 |
| 11206000 | MC 2,5 stamped | Female | 1,5-2,5 | Ag | 3,5+0,5 |



Approvals

UL-Approval , E-File-Number

E75770

Standard

Safety Standard

IEC 61984, UL1977

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

| | | |
|---|---------------------------------------|-------------|
| Creator: MANA2/PDP Released: IVSE1/PDP | Document: DB11201000EN Version: 01 | Page 1 of 1 |
|---|---------------------------------------|-------------|