

# ALGINE BACKLIGHT DRIVER

SLI035056CW\_PW

LED panel ALGINE BACKLIGHT DRIVER, with a power of 40 W, high light efficacy 138 lm/W. It is made of high-quality components, supported by a 5-year warranty. It shines with a cold light colour (6000K), which is suitable for rooms where we need to be most focused and concentrated, such as technical workstations. Designed for recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	<b>40 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>5500 lm (360°)</b>	Colour temperature	<b>6000 K</b>
Colour of light	<b>CW</b>	Beam angle	<b>120 °</b>
Degree of protection (IP)	<b>IP20</b>		


## Technical data

Code	SLI035056CW_PW
Power	40 W
Nominal current	186 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	PHILIPS
Power factor	0.9
Useful luminous flux*	5500 lm (360°)
Luminous flux**	4800 lm (360°)
Lamp efficacy	138 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	120 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x26 mm
Mounting hole	575x575mm mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC




## Related documents



 Declaration of Conformity



 Photometric file

