

PRODUCT-DETAILS

OT315KUUR3AZ

OT315KUUR3AZ EMC safety switch



General Information

Extended Product Type	OT315KUUR3AZ
Product ID	1SCA022725R2890
EAN	6417019233789
Catalog Description	OT315KUUR3AZ EMC safety switch

Long Description

EMC safety switch, 3-p. 415V AC23 315A, 160kW. Mounted auxiliary contact: 2NO1NC. Steel sheet enclosure. IP65. RedYellow Pistol handle. Interlocked cover. Defeatable interlocking. The enclosed switch is using a galvanised steel enclosure, with polyester coating. It is suitable for outdoor use with respect to UV light and ingress protection. The enclosure have inbuilt gas pressure relief function to protect the user in case of an internal arc. The door is earthed via the hinges. The enclosure is prepared for single and parallell cables. Cable entry types can be blank , ring-flange or C-flange type (FL21), with different cable configuration, like top/bottom or bottom/bottom. The handle is padlockable for 3 padlocks, cover is interlocked, and interlock function can be bypassed for thermographing.

Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC340076D0201
RoHS Information	1SCC340075D0201
Toxic Substances Control Act - TSCA	1SCC340095D0201

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363090
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC340016M0005
Mechanical Drawings	OTKM804023PBL4R.stp

Dimensions

Product Net Width	400 mm
Product Net Height	800 mm
Product Net Depth / Length	230 mm
Product Net Weight	25.57 kg

Technical

Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 315 A (500 V) 315 A (690 V) 315 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 315 A (500 V) 315 A (690 V) 315 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 160 kW (500 V) 200 kW (690 V) 250 kW
Conventional Thermal Current (I_{the})	Fully Enclosed 315 A
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I_{cm})	(1000 V AC) 65 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 15 kA
Rated Conditional Short-Circuit Current (I_{nc})	61.5 kA
Power Loss	at Rated Operating Conditions per Pole 6.5 W
Pollution Degree	3
Handle Color	Red / Yellow
Handle Type	Pistol handle
Standards	IEC 60947-1, -3
Special Functions	EMC
Number of Poles	3
Neutral Type	No neutral terminal
Connecting Capacity Main Circuit	Hole Diameter 10 mm Screw Clamp / PE Terminal 4pc, 25 ... 120 mm ²
Cable Entry Position	Bottom/Bottom
Cable Outlets Per Side	Blank / 4xring-flange, Knock-outs: 3x10mm, 12.5mm, 20.5mm, 25.5mm, 32.5mm

Degree of Protection	acc. to IEC 60529 IP65
Impact Resistance Rating	Housing IK09
Enclosure Material	Steel sheet
Maximum Mounted Auxiliary Contacts	2 NO, 1 NC
Mounted Auxiliary Contacts	2 NO, 1 NC
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	2
Tightening Torque	Main Circuit 44 N·m

Technical UL/CSA

Tightening Torque	Main Circuit 44 N·m
-------------------	---------------------

Environmental

RoHS Status	Following EU Directive 2011/65/EU
Toxic Substances Control Act - TSCA	1SCC340095D0201

Certificates and Declarations

Declaration of Conformity - CE	1SCC340025D2704
REACH Declaration	1SCC340076D0201

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	415 mm
Package Level 1 Depth / Length	910 mm
Package Level 1 Height	325 mm
Package Level 1 Gross Weight	27.7 kg
Package Level 1 EAN	6417019233789

Classifications

Object Classification Code	Q
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
eClass	V11.1 : 27371403
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Safety Switches → Enclosed Safety Switches

