

PCE data sheet

article#	9029100
article description	CEE-switched socket Sölden IV 125A 5p 6h M63oBVu Lastt.4pEa
description long	<p>thermoplastic distribution box - wall mounted - model Sölden IP66 520x297x165 13TE with external wall mounting brackets 1xM63 cable gland on top (cable diameter 34-44mm PG48) black 1x blind cable gland M63 from bottom 1xCEE-socket 125A 5p 400V with PCS system protected with circuit breaker 125A 4p with integrated low voltage circuit breaker (for 125A) control circuit protected with MCB 2A 2p C MCB made by Eaton OVE / VDE circuit breaker made by Eaton OVE / VDE TYP NZM1 thermic release distribution box is wired on terminals 5x50qmm task: Through the PCS system in connection with the switch disconnecter including undervoltage release will be the tension-free plugging and pulling on the socket 125A guaranteed in addition the sockets are secured against automatic resetting after power failure of the supply line.</p>
GTIN (EAN)	9003399981333
country of origin	AT
customs number	85371098
net weight	10.000 kg
packaging quantity	1



ETIM 7.0	EC001324
IEC-amperage	125 A
Number of poles	5
Voltage acc. EN 60309-2	400 V (50+60 Hz) red
Clock hour position	6 h
Identification colour	Red
Degree of protection (IP)	IP54
Switch	Electrical locking
Material housing	Plastic
Model	Base unit and cover
Contact material	CuZn
Surface finish contacts	Nickel-plated

wire flexible	16-50 mm ²
wire solid	16-70 mm ²



www.manufacturer-safety.info