

PRODUCT-DETAILS

MCB-20B MCB-20B Contact Block



Extended Product Type	MCB-20E
Product ID	1SFA611610R2002
EAN	7320500544433
Catalog Description	MCB-20B Contact Block
Long Description	The MCB-20B Contact Block is: Without holder - Non-illuminated - Double contact block - Rear mounting - silver (Ag) - 2 NO - 0NC - 690 V This Contact Block is part of ABB's modular plastic range, the most versatile range with a high level of flexibility and market-leading electrical ratings. Engineered for total reliability, longer lifetime, and highest mechanical durability. Self-cleaning contacts ensure reliable operation without the need for maintenance, increasing uptime. A high degree of protection guarantees reliability in extreme environments. The innovative design simplifies the entire process, from selection to easy and quick, tool-free installation. The perfect solution for every application
Ordering	
Ordering Minimum Order Quantity	10 piece
<u> </u>	10 piece 8536901000
Minimum Order Quantity Customs Tariff Number	
Minimum Order Quantity	

Dimensions	
Product Net Width	0.02 m
Product Net Height	0.044 m
Product Net Depth / Length	0.028 m
Product Net Weight	0.04 kg

Technical	
Ambient Air Temperature	Operation -25 +70 °C Storage -40 +85 °C
Illumination	Non-illuminated
Function	Without holde
Mounting Type	Rear mounting
Number of Auxiliary Contacts NC	(
Number of Auxiliary Contacts NO	2
Degree of Protection	Terminals IP20
Pollution Degree	
Rated Insulation Voltage (U _i)	690 \
Rated Impulse Withstand Voltage (U _{imp})	6 k\
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	Maximum 690 \
Rated Operational Current DC-13 (I _e)	(24 V) 5 4 (125 V) 0.55 4
Rated Operational Current AC-15 (I _e)	(230 V AC) 6 A
Power Loss	Maximum 5 W
Mechanical Durability	10 millior
Connecting Capacity	Flexible with Ferrule 1 x 0.752.5 mm Flexible with Ferrule 2 x 0.752.5 mm Flexible with Insulated Ferrule 1 x 0.752.5 mm Flexible with Insulated Ferrule 2 x 0.752.5 mm Flexible 1 x 0.75 2.5 mm Flexible 2 x 0.75 2.5 mm Solid 1 x 0.752.5 mm Solid 2 x 0.752.5 mm
Connection Type	Screw Clamp
Terminal Type	Screw Terminals
Tightening Torque	0.9 N·n
Wire Stripping Length	8 mr
Suitable For	MP MP2 MP2 MP2 MPD MPD1 MPD1 MPD1 MPD12 MPD12 MPD13 MPD13 MPD14 MPD15 MPD14 MPD15 MPD16 MPD15 MPD16 MP

MPEP4 MPEK4 MPMT3

Suitable	e for	Prod	uct	Class

Technical UL/CSA	
Connecting Capacity	1x 1814 AWG
UL/CSA	2x 1814 AWG

Environmental	
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	0635 4
RoHS Information	2CMT2015-005452
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business

Certificates and Declarations	
CB Certificate	SEMKO_SE30016M2
CQC Certificate	CQC2005010304154103
cULus Certificate	UL-E76003-20140513
Declaration of Conformity - CCC	2020980305001528
Declaration of Conformity - CE	2CMT2015-005452
Declaration of Conformity - UKCA	2CMT2020-006121
DNV GL Certificate	E-14107

Container Information	
Package Level 1 Units	bag 10 piece
Package Level 1 Width	0.11 m
Package Level 1 Depth / Length	0.15 m
Package Level 1 Height	0.02 m
Package Level 1 Gross Weight	0.4 kg
Package Level 1 EAN	7320500307823

Classifications	
Object Classification Code	S
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
eClass	V11.0 : 27371302
UNSPSC	39122221
IDEA Granular Category Code (IGCC)	5219 >> Switch part or accessory
E-Number (Finland)	2339559
E-Number (Norway)	4372993
E-Number (Sweden)	3717130

Categories

Low Voltage Products and Systems \rightarrow Control Products \rightarrow Pilot Devices \rightarrow Modular Plastic Range Medium Voltage Products and Systems \rightarrow Service \rightarrow Spares and Consumables \rightarrow Parts \rightarrow All Spare Parts (Relays-SWG-CB)

