



MASTER - LED HID SON-T

MAS LED SON-T IF 9Klm 50W 740 E40

Philips LED Road lamps are an easy LED solution with a short payback period to replace High Intensity Discharge (HID) and High Pressure Sodium (SON) lamps. TrueForce LED solutions bring the energy efficiency and long lifetime benefits of LED to HID replacement, providing instant savings for a low initial investment. With the right lamp size and light distribution, you can easily retrofit TrueForce LED road lamps into existing SON and SON-T systems, enhancing the lighting quality with LED without changing the luminaire's ballast or reflector.

Warnings and Safety

• Installation should always be performed by a qualified electrician or installer. Use the installation guide for instructions.

Product data

General Information	
Cap-Base	E40 [E40]
EU RoHS compliant	Yes
Nominal lifetime	70,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	740 [CCT of 4000K]
Luminous Flux	9,000 lumen
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	180 lm/W
Color Consistency	<6

Color rendering index (CRI)	70
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	50 Hz
Input Frequency	50 Hz
Power Consumption	50 W
Lamp Current (Nom)	1,060 mA
Wattage Equivalent	100 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Voltage (Nom)	85-95 V
Temperature	
Ambient temperature range	-40 °C to 55 °C


Datasheet, 2023, May 5 data subject to change

MASTER - LED HID SON-T

T-Case Maximum (Nom)	52 ℃
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Glass
Bulb Shape	T70 [T 70mm]
Approval and Application	
Energy Consumption kWh/1000 h	50 kWh
EPREL Registration Number	1,077,806


871951444897100
MAS LED SON-T IF 9Klm 50W 740 E40
929003467512
1
6
929003467512
0.490 kg
MAS LED SON-T IF 9Klm 50W 740 E40
8719514448988

Dimensional drawing




Product	D	С
MAS LED SON-T IF 9Klm 50W 740 E40	71 mm	262 mm

Photometric data









MASTER - LED HID SON-T


Photometric data



Spectral Power Distribution Colour

Lifetime





Life Expectancy Diagram - MAS LED SON-T IF 9Klm 50W 740 E40

Lumen Maintenance Diagram - MAS LED SON-T IF 9Klm 50W 740 E40



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.