



# CorePro LED PLL

## CorePro LED PLL EM/Mains 12W 830 4P

Philips CorePro LED PLL is the ideal uplamping solution for downlights & luminaires in a wide range of general lighting applications. It integrates a LED light source into a traditional fluorescent form factor to offer superb energy savings over a lifetime that's twice as long as fluorescent alternatives.

### Product data

General Information	
Cap-Base	2G11 [2G11]
Nominal lifetime	30,000 hour(s)
Switching Cycle	200,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	160 degree(s)
Luminous Flux	1,440 lumen
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	120 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	12 W
Lamp Current (Nom)	60 mA


Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	220-240 V
Temperature	
Ambient temperature range	-20 °C to 45 °C
T-Case Maximum (Nom)	70 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Material	Glass
Product Length	300 mm
Bulb Shape	Tube, single-ended
Approval and Application	
Energy Saving Product	Yes
Approval Marks	RoHS compliance TUV CE marking KEMA Keur certificate
Energy Consumption kWh/1000 h	12 kWh

# CorePro LED PLL

EPREL Registration Number	1,370,825
EU RoHS compliant	Yes
<b>Product Data</b>	
Full product code	872016915703300
Order product name	CorePro LED PLL EM/Mains 12W 830 4P
Order code	929003592402
Numerator - Quantity Per Pack	1



Numerator - Packs per outer box	10
Material number (12NC)	929003592402
Net weight	0.113 kg
Full product name	CorePro LED PLL EM/Mains 12W 830 4P
EAN/UPC - Case	8720169157040

## Dimensional drawing




Product	D1	D2	A1	A2	A3
CorePro LED PLL EM/Mains 12W 830 4P	17 mm		250 mm	312 mm	319 mm

## Photometric data





Spectral Power Distribution Colour

Light Distribution Diagram





# CorePro LED PLL

## Lifetime




Lumen Maintenance Diagram

Life Expectancy Diagram



Life Expectancy Diagram - CorePro LED PLL EM/Mains 12W 830 4P

Life Expectancy Diagram



Lumen Maintenance Diagram - CorePro LED PLL EM/Mains 12W 830 4P

## CorePro LED PLL

