

# PRODUCT DATASHEET DULUX S 11 W 2700 K G23

# OSRAM DULUX® S | Short CFLni, with 2-pin base for CCG operation



#### Areas of application

- Ideal for cost-effective creative illumination and decoration
- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants

## **Product benefits**

- Improved maintenance

## **Product features**

- Good color rendering index
- Short and compact pin-base lamps with single-turn tubes
- Single-ended two-pin plug-in G23 base



## **TECHNICAL DATA**

## **Electrical data**

Nominal wattage	11 W
Construction wattage	11.00 W

## Photometrical data

Luminous flux	900 lm
Light color (designation)	LUMILUX INTERNA
Color temperature	2700 К
Color rendering index Ra	≥ 80
Light color	827

# **Dimensions & Weight**

Overall length	234.50 mm
Diameter	12.00 mm
Product weight	35.11 g

# Lifespan

Lifespan	0 relevant

## Additional product data

Base (standard designation)	G23
Mercury content	1.3 mg

# Capabilities

Dimmable	No

# Country-specific categorizations

Order reference	DULUX S 11W/827

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G23
Length	237.00 mm
Height	12.00 mm
Width	12.00 mm

## **EQUIPMENT / ACCESSORIES**

- Suitable for operation on conventional control gear

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321580771	Folding box 1	36 mm x 23 mm x 239 mm	45.10 g	0.20 dm <sup>3</sup>
4052899226869	Shipping box 10	123 mm x 78 mm x 252 mm	517.00 g	2.42 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.