



## D-sub interface 37 poles female slim

|   |                                 |
|---|---------------------------------|
| <b>Series</b>                                   | CPD                             |
| <b>Code</b>                                     | XCPD37F                         |
| <b>Type</b>                                     | CPD37F                          |
| <b>HS code</b>                                  | 85369010                        |
| <b>GENERAL TECHNICAL DATA</b>                   |                                 |
| <b>Number of poles</b>                          | 37                              |
| <b>Version</b>                                  | D-sub female                    |
| <b>Input rated voltage</b>                      | 0...25 Vac / 0...60 Vdc         |
| <b>Input rated current</b>                      | 2 A max                         |
| <b>Operating temperature range</b>              | -20...+60°C                     |
| <b>Oversvoltage category / pollution degree</b> | II / 2                          |
| <b>Protection degree</b>                        | IP 00                           |
| <b>Connection terminal</b>                      | 2.5 mm <sup>2</sup> screw       |
| <b>Dimensions (LxHxD)</b>                       | 77x80x93 mm                     |
| <b>Housing material</b>                         | UL94V-0 plastic material        |
| <b>Mounting information</b>                     | vertical on rails, side by side |
| <b>ACCESSORIES</b>                              |                                 |
| <b>Mounting rail (IEC60715/TH35-7.5)</b>        | PR003, PR903, PR005, PR921      |
| <b>Mounting rail (IEC60715/TH35-15)</b>         | PR007, PR907, PR006, PR922      |
| <b>APPROVALS AND MARKINGS</b>                   | CE                              |



\* Universal module\* Compact dimensions  
1 The terminal number corresponds to the connector number

## DESCRIZIONE DEL PRODOTTO

CPD37F D-sub interface 37 poles female slim