



Plusline ES Compact

Plusline 78mm 2y 80W R7s 230V 1BB

Mains-voltage halogen linear lamp with superior quality and reliability. Offers very long lifetime and crisp halogen light. Ideal solution for decorative luminaires.

Product data

General information					
Cap-Base	R7S [R7s]				
Operating Position	UNIVERSAL [Any or Universal (U)]				
Nominal Lifetime (Nom)	2000 h				
Switching Cycle	8000X				
Rated Lifetime (Hours)	2000 h				
Light technical					
Luminous Flux (Nom)	1415 lm				
Luminous Flux (Rated) (Nom)	1415 lm				
Correlated Color Temperature (Nom)	2900 K				
Luminous Efficacy (rated) (Nom)	17.5 lm/W				
Color Rendering Index (Nom)	100				
LLMF at End of Nominal Lifetime (Min)	80 %				
Operating and electrical					
Power (Nom)	80.0 W				
Lamp Current (Nom)	0.35 A				
Starting Time (Nom)	0.0 s				
Warm Up Time to 60% Light (Nom)	instant full light				
Power Factor (Nom)	1				
Voltage (Nom)	230 V				
Controls and dimming					
Dimmable	Yes				

Mechanical and housing				
Bulb Finish	Clear			
Cap-Base Information	18			
Bulb Shape	T11 [T 11mm]			
Approval and application				
Energy Consumption kWh/1000 h	80 kWh			
Luminaire design requirements				
Bulb Temperature (Max)	900 ℃			
Pinch Temperature (Max)	350 °C			
Product data				
Full product code	872790085228800			
Order product name	Plusline 78mm 2y 80W R7s 230V 1BB			
EAN/UPC - Product	8727900852288			
Order code	924587144210			
Numerator - Quantity Per Pack	1			
Numerator - Packs per outer box	100			
Material Nr. (12NC)	924587144210			
Copy Net Weight (Piece)	5.380 g			

Datasheet, 2022, August 7 data subject to change

Plusline ES Compact

Dimensional drawing



Product	D (max)	B (max)	В	B (min)	C (max)
Plusline 78mm 2y 80W R7s	11 mm	76.5 mm	74.9 mm	73.3 mm	78 mm
230V 1BB					

Plusline 78mm 2y 80W R7s 230V 1BB

