



MASTER TL-D 90 De Luxe

MASTER TL-D 90 De Luxe 18W/940 SLV/10

This TL-D lamp makes colors appear rich, deep and enhanced in a natural way. Thus very suitable for applications where a high color recognition is needed: first aid and treatment rooms in hospitals, printing rooms, jewelry, dentists, hairdressing, museums and shops

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Life To 10% Failures (Nom)	12000 h
Life to 50% Failures (Nom)	15000 h
Life to 50% Failures Preheat (Nom)	20000 h
LSF 2000 h Rated	99 %
LSF 4000 h Rated	99 %
LSF 6000 h Rated	99 %
LSF 8000 h Rated	99 %
LSF 12000 h Rated	89 %
LSF 16000 h Rated	33 %
LSF 20000 h Rated	2 %
Light technical	
Color Code	940 [CCT of 4000K]
Luminous Flux (Nom)	1200 lm

Color Designation	Cool White (CW)
Chromaticity Coordinate X (Nom)	0.38
Chromaticity Coordinate Y (Nom)	0.38
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	65.2 lm/W
Color Rendering Index (Nom)	91
LLMF 2000 h Rated	96 %
LLMF 4000 h Rated	95 %
LLMF 6000 h Rated	94 %
LLMF 8000 h Rated	93 %
LLMF 12000 h Rated	92 %
LLMF 16000 h Rated	91 %
LLMF 20000 h Rated	90 %
Operating and electrical	
Power (Nom)	18.0 W


Datasheet, 2022, July 28 data subject to change

MASTER TL-D 90 De Luxe

Lamp Current (Nom)	0.360 A
Temperature	
Design Temperature (Nom)	25 °C
Controls and dimming	
Dimmable	Yes
Mechanical and housing	
Bulb Shape	T8 [26 mm (T8)]
Approval and application	
Mercury (Hg) Content (Nom)	1.7 mg
Energy Consumption kWh/1000 h	22 kWh

Product data	
Full product code	871150088839625
Order product name	MASTER TL-D 90 De Luxe 18W/940 SLV/10
EAN/UPC - Product	8711500888396
Order code	928043594081
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	928043594081
Copy Net Weight (Piece)	71.000 g
ILCOS Code	FD-18/38/1A-E-G13

Dimensional drawing




 Product
 D (max)
 A (max)
 B (max)
 B (min)
 C (max)

 MASTER TL-D 90 De Luxe
 28 mm
 589.8 mm
 596.9 mm
 594.5 mm
 604 mm

 18W/940 SLV/10

MASTER TL-D 90 De Luxe 18W/940 SLV/10

Photometric data





LDPB_TL-D9HLm_940-Spectral power distribution B/W

LDPO_TL-D9HLm_940-Spectral power distribution Colour


MASTER TL-D 90 De Luxe


Lifetime





LDLE_TL-D9HLm_0002-Life expectancy diagram





LDLM_TL-D9HLm_0001-Lumen maintenance diagram



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.