

PRODUCT DATASHEET SMART+ Wifi Orbis Wall Cylindro 200X127mm Black TW

Smart+ Orbis Cylindro | Smart decorative wall lamp with wifi technology TW and dimmable, up and down



Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

Product benefits

- Easy and quick installation

Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Dimmable
- Network protocol: WiFi



TECHNICAL DATA

Electrical data

Nominal wattage	12.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	55.000 mA
Inrush current	3.67 A
Power factor λ	> 0.90
Total harmonic distortion	< 20 %
Protection class	П
Operating mode	External LED driver

Photometrical data

Luminous flux	700 lm
Total luminous flux of contained light sources	1200 lm
Luminous efficacy	68 lm/W
Color temperature	30006500 K
Reference control setting of contained light source (Kelvin)	3000 K ¹⁾
Light color (designation)	Tunable White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	360 °

¹⁾ Performing a reset will restore the default values set by the manufacturer

Dimensions & Weight

Length	127.00 mm
Width	95.00 mm
Height	200.00 mm
Product weight	560.00 g

SMART WIFI ORBISW CYLDRO

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Screw terminal
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Mounting location	Wall
Application environment	Indoor
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

Emergency lighting

Integrated test switch	No
integrated test switch	NO

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

EQUIPMENT / ACCESSORIES

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

Documents and certificates		Document name	
User instruction / safety instructions SMART WIFI ORBISW CROSS CYLD		SMART WIFI ORBISW CROSS CYLDRO TWIST	
PDF	Legal information	Legal insert Residential luminaires	
PDF	Declarations of conformity	EC declaration_Wall lamp	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075574212	Folding box 1	136 mm x 100 mm x 240 mm	656.00 g	3.26 dm ³
4058075574229	Shipping box 4	290 mm x 216 mm x 260 mm	3129.00 g	16.29 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.